
SWSLOBO7HDElectric Hydraulic-drive Scissor-type Aerial Work Platform


SUNW\(\hat{N}\)RD

Dim	ension	
Work	ing height*	8m
Α	Platform height maximum	6m
В	Platform height (stowed)	1.05m
С	Platform length	1.7m
	Slide-out platform extension deck	0.9m
D	Platform width	0.74m
Е	Stowed height (rails up)	2.17m
	Stowed height (rails down)	1.79m
F	Overall length	1.86m
G	Overall width	0.76m
Н	Wheelbase	1.38m
I	Ground clearance (stowed)	0.07m
J	Ground clearance (raised)	0.02m

0 10	
	A

Performance	
Lift capacity	230kg
Lift capacity (extension deck)	113kg
Max. platform pecupancy	2
Drive speed (stowed)	3.0km/h
Drive speed (elevated)	0.8km/h
Turning radius (inside)	0m
Turning radius (outside)	1.67m
Raise / lower speed	20s / 27s
Gradeability**	25%
Max. allowable working angle (lateral / longitudinal)	1.5° / 3°
Controls	Proportional
Wheel driver	Dual front wheel
Multiple disc brakes	Dual rear wheel
Tires	305mm×100mm
Battery	4×6V/225Ah
Charger	24V/30A
Weight	1530kg





^{*} Working height is equal to Platform height plus 2m.

^{*} Climbing ability is suitable for driving on slopes; Refer to Operator Manual for slope level.

SWSL0807HD

Electric Hydraulic-drive Scissor-type Aerial Work Platform











Standard features

Proportional control	Extended platform	◆ Folding guardrails platform	◆ Self-lock gate on platform
• Solid tire	Hour meter	Standard transport forklift hole	Safety maintenance support rod
• Horn	Flashing beacon	Action beep	◆ Dual front wheel drive
Pit protection device	Emergency descent system	◆ Emergency stop button	Automatic brakes system
◆ Tilt sensor with alarm	◆ Charging protection system	◆ Fault diagnosis system	◆ Overload protection system

Options features

◆ Air line to platform	◆ AC power to platform	◆ GPS tracking system	◆ Platform work lights
◆ Maintenance-free battery	Lithium battery and management system	◆ Intelligent interconnection system	

